EN

Electrohydraulic in-row weeder adaptable to all frames or cultivators


















Electrohydraulic in-row weeder adaptable to all frames or cultivators for mechanical weeding or tillage inside rows (mainly vineyards and fruit trees).



PICTURE MODEL:

IA-D + VO-D

















Versatility

- The widest range of produtcs and accessories on the market. A custom configuration to suit your needs.
- The ID-CONTROL joystick allows to control all the machines manufactured by ID David and equipped with the ID-PLUS or ID-MICRO technology.
- Different tools that allow both surface and tillage works up to 20 cm deep.



Exclusivity

- The exclusive undervine weeder that combines the "parallelogram-radial" movement.
- Faster, safer and endowed with unmatched versatility thanks to its triple tool holder.
- The adjustable and progressive electronic sensor allows a safe working under plants from 1 cm diameter, the parallelogram moves at right time to save the plant.



Effectiveness

- Time is valuable, it is possible to work up to 12 km/h with a standard soil conditions.
- The easy adjusting of hydraulic pressure of the in row weeder assured a perfect work in any type of soil.

(I) Reliability

- Components and materials of high quality from certified manufacturers.
- · Heavy duty frame and robotic welding.
- Experience on manufacturing of electrohydraulic in-row weeder since 1974.



- As standard all models are fitted with an exclusive safety locking system in case of faults
- Enables route deviations up to 30 cm in the plantation'rows.
- Our equipment incorporates easy, comfortable and safe tool replacement systems.



Sustainability

- Ecological alternative to the use of herbicides
- Our painting is lead-free and without toxic pigments.
- Improves the structure and porosity of the soil.

Standard Equipment

- · Anti-shock sensor protector.
- Box + flange for frame or cultivator assembly.
- Hydraulic pressure regulator.
- Tool kit for sensor regulation.
- Arm "D" and Plough blade to weed manufactured in boron steel.
- · Special testrod sensor in high tensile steel.
- Security system under damages.
- · Self standing taster height adjustable.
- · Electronic inductive sensor.
- · Connection valve direct to tractor.

Remote control type

ID-PLUS

- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 5 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

ID-MICRO

- ! NOT included the ID-CONTROL multifunction joystick.
- Only for customers who already have the ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 5 additional electro-hydraulic functions
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

ID-BASIC

- · Includes an electric control box.
- Max. 1 additional electro-hydraulic function to choose between: PI-002 / PI-004 / IH-EC
- ! NOT allowed any updates of electrohydraulic functions.


			ID-PLUS	ID-MICRO	ID-BASIC
ID-WEEDE	ER	cm	REF.	REF.	REF.
СОМРАСТ		49	IAC-1-D	IAC-2-D	IAC-3-D
COMPACI		49	IAC-1-P	IAC-2-P	IAC-3-P
STANDARD		55	IA-1-D	IA-2-D	IA-3-D
SIANDARD		55	IA-1-P	IA-2-P	IA-3-P
LARGE		65	IAL-1-D	IAL-2-D	IAL-3-D
LARGE		65	IAL-1-P	IAL-2-P	IAL-3-P







Technical details

		х			50	L	w	Н
ID-WEEDER	REF.	m	kg	m	HP	m	m	m
СОМРАСТ	IAC-D	0,75	70	≤1	30	0,45	0,65	0,60
COMPACT	IAC-P	0,75	135	≤1	35	0,45	0,65	0,60
STANDARD	IA-D	1,00	70	≤1	30	0,60	0,75	0,60
SIANDARD	IA-P	1,00	135	≤1	35	0,60	0,75	0,60
LARGE	IAL-D	1,10	70	≤2	30	0,60	0,85	0,60
LARGE	IAL-P	1,10	135	≤2	35	0,60	0,85	0,60







Pre-installations and updates Accessories and Options

)	DESCRIPTION	OBSERVA	ATIONS	REF.
	Pre-installation in-row weeder left side/electrohydraulic system			PI-001
	Pre-installation solenoid valve	1 extra function double acting	for ID-BASIC	PI-002
		on/off motorized tools	IOI ID-BASIC	PI-004
Quick connection kit for power tools				KC-001

Undervine weeders

Accessories and Options

0	DESCRIPTION	OBSERVATION	REF.	
	Hydraulic power PRO unit 22L with pump 27L	Adaptable to frame	-2	CPRO-0
	Standard oil cooler	Adaptable to PRO hydraulic power plant	Intake 12V	A15-01-PRO
	Pressure filter kit + oil cooler	Tractor plugs connection	Intake 12V	KFP-02

0	DESCRIPTION	OBSERVATIONS		REF.	
	Hydraulic side slope correction for in- row weeders	Directly to the tractor	Unit +2	IH-DT	
	Increases working width of 10 cm Inclination: + 21°, -10°	Electric cabine	Unit	IH-EC	
	Grass bend down system	_	Right	STH-D	
	Grass bend down system		Pair	STH-P	
."/	Ultrasensible kit for sensitive sensor	Ideal vineyards ≤ 1 cm	Unit	KU-1	
	Reinforced in row weeder cylinder for hard soil	Replaces standard cylinder. Recommended oil cooler.	Unit	CIA-R	
Ô		for ID-PLUS /	Right	MD1-D	
ノ)	Distance Control with cable	ID-MICRO	Pair	MD1-P	
	Distance Control With Cable	for ID-BASIC —	Right	MD2-D	
			Pair	MD2-P	
	Electrohydraulic kit for quick- connection	In row weeder connection- disconnection	Right	KER-IA-D	
	(connection-disconnection)	Not available for ID- BASIC	Pair	KER-IA-P	
	Additional extension (female-female)		120 mm	SE1-HH	
	Additional extension (lemate-lemate)		200 mm	SE2-HH	
	Additional extension of 120mm (male-female)			SE-MH	
•	Adjustable row cleaner disc 11"	Adaptable to in-row	Right	BPI-D	
•	(smooth disc)	weeder	Pair	BPI-P	
•	Adjustable row cleaner disc 13"	Adaptable to in-row	Right	BPID-D	
	(notched disc)	weeder	Pair	BPID-P	
	Storage foot and frame equipped with wheels		Right	PAIR-D	

Undervine weeders Tools for PARALLELOGRAM USE P

	0	DESCRIPTION	OBSERVATIONS		REF.
Р		Shoot remover kit + Sensor rod + String spool	IA-C IA		DBR25-1-D
		250 mm working width	IAL	Right	DBR25-2-D
		*Recommended oil cooler Available only for vineyards with at least 40 cm free to the ground or to any obstacle	IA-C IA	Pair —	DBR25-1-P
			IAL	raii	DBR25-2-P
D	Cast	Arm B + fixed ploughshare + Sensor rod kit	310x480x400mm	Right	BB-VFD
P (Pair	BB-VFP
		Arm C + adjustable ploughshare + sensor rod kit	410x540x430mm	Right	BC-VRD
				Pair	BC-VRP


	0	DESCRIPTION	OBSERVATIONS		REF.
D		Arm E + fixed ploughshare with ridging		Right	BE-VFD
		element + sensor rod kit		Pair	BE-VFP
	4	Retractable extra cleaner blade with		Right	EM-D
		spring for ploughshare		Pair	EM-P
	Undervine Tools for	weeders RADIAL USE R			
R		Arm D + weeding blade +	Standard included	Right	BD-CPD
		sensor rod kit		Pair	BD-CPP
•	-			Cut 49 cm	RCI49D
U		Kit weeding blade + sensor rod	Right	Standard 55 cm	RCI55D
				Long 65 cm	RCI65D
				Cut 49 cm	RCI49P
R		Kit weeding blade + sensor rod	Pair	Standard 55 cm	RCI55P
				Long 65 cm	RCI65P
ß		Kit weeding blade made by Tugstene + sensor rod	Right	– Standard 55 cm —	RCHD55D
ß		Kit weeding blade made by Tugstene + sensor rod	Pair	Standard 35 cm	RCHD55P
	Retractable	Retractable extra cleaner blade "V" for		Right	EV-D
•	4	blade		Pair	EV-P
		Blade shovel		Right	VO-D
				Pair	VO-P
		Kit mini reversible plough kit 2 discs Ø13.5" + sensor rod 250 mm working width Recommended oil cooler and reinforced cylinder	IA-C IA	– Right —	MAD25-1-D
P			IAL		MAD25-2-D
•			IA-C IA	- Pair —	MAD25-1-P
			IAL	raii	MAD25-2-P
		Kit mini reversible plough kit 3 discs	IA-C IA	– Right —	MAD35-1-D
_		Ø13.5" + sensor rod 350 mm working width	IAL	5	MAD35-2-D
B			IA-C IA	– Pair —	MAD35-1-P
		Recommended oil cooler and reinforced cylinder	IAL	raii —	MAD35-2-P

_	0	DESCRIPTION	OBSER ¹	VATIONS	REF.
		Retractable extra cleaner blade for mini		Right	EMD-D
		harrow disc		Pair	EMD-P
		Kit Rotary hoe Ø300mm +	IA-C IA	– Right -	RA30-1-D
e		sensor rod	IAL	Rigiit	RA30-2-D
		*Possibility of simultaneous use with weeding blade (not	IA-C IA	— Pair -	RA30-1-P
_		included) Recommended oil cooler + reinforced cylinder	IAL	. 4	RA30-2-P
		Kit Rotary hoe Ø400mm +	IA-C IA	– Right -	RA40-1-D
ß		Sensor rod	IAL	5	RA40-2-D
		*Possibility of simultaneous use with weeding blade (not	IA-C IA	— Pair -	RA40-1-P
_		included) Recommended oil cooler + reinforced cylinder	IAL	raii	RA40-2-P
		Kit Rotary hoe Ø500mm +	IA-C IA	– Right -	RA50-1-D
•		Sensor rod	IAL	Rigit	RA50-2-D
w		,	IA-C IA	— Pair -	RA50-1-P
_		Recommended oil cooler and reinforced cylinder	IAL	raii	RA50-2-P
		Kit string mower Ø400mm + Sensor rod + String reel	IA-C IA	– Right -	GS40H-1-D
ß			IAL	Rigiit	GS40H-2-D
			IA-C IA	— Pair -	GS40H-1-P
_		Recommended oil cooler and reinforced cylinder	IAL	raii	GS40H-2-P
		Kit string mower Ø500mm + Sensor rod +	IA-C IA	– Right -	GS50H-1-D
		String reel	IAL	Night	GS50H-2-D
R			IA-C IA	— Pair -	GS50H-1-P
_		Recommended oil cooler and reinforced cylinder	IAL	T GII	GS50H-2-P
		Kit string mower Ø600mm + Sensor rod + String reel	IA-C IA	– Right -	GS60H-1-D
e	3		IAL	Night	GS60H-2-D
•			IA-C IA	— Pair -	GS60H-1-P
_		Recommended oil cooler and reinforced cylinder	IAL	raii	GS60H-2-P
	4	Kit for modification of string mower	Only available for new _ machine		KSGSH-D
_		with boron steel blades		Pair	KSGSH-P
_		Square string spool	for mower	45 m	BHN-03
		Nylon string blue spool	for brush head	90 m	BHN-01
®		Herbicide application head	Ø500 —	Right	AH50D
_		• •		Pair	AH50P
		Packaging	Basic Airfreight- oceanfreight	ht	EMB-1
_	***************************************		All Height- oceanfreigh	III.	EMB-2



Ideal products and services that inspire trust, quality, experience and excellence

Specialized and customized agricultural machines with an attractive design and increasing digitalizations. Our products are oriented towards a biological, environment-friendly and precision farming.





INDUSTRIAS DAVID S.L.U.

C/ Médico Miguel Lucas s/n CP: 30510, Yecla, Murcia-Spain Tel.: +34 968 718 119 info@id-david.com

Connect with us.

instagram.com/iddavid_official twitter.com/IDdavidslu facebook.com/industriasdavid linkedin.com/company/id-david youtube.com/industriasdavid

www.id-david.com





















