
# **ID-NAMIC**

Reversible and extendable frame with undervine weeder to 3P hitching












EN



**Reversible and extendable frame with undervine weeder to 3P hitching**, perfect to tillage and weeding between plants rows.











# 🔆 Versatility

- The widest range of produtcs and accessories on the market. A custom configuration to suit your needs.
- Different tools that allow both surface and tillage works up to 20 cm deep.
- The ID-CONTROL joystick allows to control all the machines manufactured by ID David and equipped with the ID-PLUS or ID-MICRO technology.

# 🕘 Reliability

- Components and materials of high quality from certified manufacturers.
- Heavy duty frame and robotic welding.
  Experience in the manufacture of electrohydraulic undervine weeders sin
- electrohydraulic undervine weeders since 1974.
- Great visibility of the rows.

# 🙆 Exclusivity

- The exclusive undervine weeder that combines the "parallelogram-radial" movement.
- Faster, safer and endowed with unmatched versatility thanks to its triple tool holder.
- Opportunity to work between plants starting from 1 cm diameter thanks to our adjustable and progressive eletronic sensor, the arm is moving at the right time to save the plant.

# 🕑 Safety

- As standard all models are fitted with an exclusive safety locking system in case of faults.
- Enables route deviations up to 30 cm in the plantation'rows.
- Our equipment incorporates easy, comfortable and safe tool replacement systems.

## 💮 Effectiveness

- Time is valuable, it is possible to work up to 12 km/h with a standard soil conditions.
- The easy adjusting of hydraulic pressure of the in row weeder assured a perfect work in any type of soil.

# 🕉 Sustainability

- Ecological alternative to the use of herbicides.
- The low power required allows the use of small tractors with a lower carbon footprint.
- Improves the structure and porosity of the soil.

# <u>Undervine Weeding</u>

#### **Standard Equipment**

- Includes a PRO hydraulic unit.
- Anti-shock sensor protector.
- Reversible chassis for use in front and rear 3rd point.
- Hydraulic pressure regulator.
- Electro hydraulic in row weeder.
- Hydraulic width adjusting to the tractor.Tool kit for sensor regulation.
- Arm "D" and blade manufactured in boron steel.

#### **Remote control type**

#### **ID-PLUS**

- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 5 additional electro-hydraulic functions.
- Includes a modular electrohydraulic system: it allows to increase the number of electrohydraulic functions.

#### ID-MICRO

- ! NOT included the ID-CONTROL multifunction joystick.
- Only for customers who already have the ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
  - Up to 5 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

#### • Quick coupling kit for power tools.

- Special rod sensor in high tensile steel.
  - Pair of metallic notched wheels width and height adjustable.
- Storage foot.
- Quick coupling. Smooth wheels mounted on the front of the frame (CR-XS and
- CR-XXS models). Wheels assembly on the extension model CR
- Wheels assembly on the extension model CR-MAX.

#### **ID-BASIC**

- Includes an electric control box.
- Max. 1 additional electrohydraulic function to choose between: PI-O02 / PI-O04 / EH-EC / CRA-EC / IH-EC
- ! NOT allowed any updates of electro-hydraulic functions.

#### **ID-PLUS DUAL**


- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes cooler and double pump.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electrohydraulic functions.
- Includes a modular electrohydraulic system: it allows to increase the number of electrohydraulic functions.

	_					
			ID-PLUS	ID-MICRO	ID-BASIC	ID-PLUS DUAL
	<u>s</u>	₽ ₽ X ₽				
<b>ID-NAMIC</b>	cm	m	REF.	REF.	REF.	REF.
1 IN ROW WEEDER	49	≥ 1,50	CR-XS-1-D	CR-XS-2-D	CR-XS-3-D	CR-XS-4-D
	55	≥ 1,85	CR-S-1-D	CR-S-2-D	CR-S-3-D	CR-S-4-D
	55	≥ 2,45	CR-M-1-D	CR-M-2-D	CR-M-3-D	CR-M-4-D
	65	≥ 2,90	CR-L-1-D	CR-L-2-D	CR-L-3-D	CR-L-4-D
2 IN ROW WEEDER	49	1,35-1,70	CR-XXS-1-P	CR-XXS-2-P	CR-XXS-3-P	CR-XXS-4-P
	49	1,50-2,05	CR-XS-1-P	CR-XS-2-P	CR-XS-3-P	CR-XS-4-P
<b>.</b>	55	1,85-2,60	CR-S-1-P	CR-S-2-P	CR-S-3-P	CR-S-4-P
	55	2,45-3,20	CR-M-1-P	CR-M-2-P	CR-M-3-P	CR-M-4-P
$\rightarrow$	65	2,90-4,00	CR-L-1-P	CR-L-2-P	CR-L-3-P	CR-L-4-P
	65	3,50-5,00	CR-MAX-1-P	CR-MAX-2-P	CR-MAX-3-P	CR-MAX-4-P





Tech	nical details		х		50	L	w	н
	ID-NAMIC	REF.	m	kg	HP	m	m	m
		CR-XS-D	≥ 1,50	300	30	1,00	0,90	1,30
	1 IN ROW WEEDER	CR-S-D	≥ 1,85	320	35	1,30	1,05	1,30
		CR-M-D	≥ 2,45	400	40	1,15	1,60	1,30
		CR-L-D	≥ 2,90	410	45	1,15	1,90	1,30
		CR-XXS-P	1,35–1,70	350	35	1,70	0,80	1,30
		CR-XS-P	1,50-2,05	350	35	1,00	1,00	1,30
		CR-S-P	1,85-2,60	370	40	1,30	1,35	1,30
	2 IN ROW WEEDER	CR-M-P	2,45-3,20	450	45	1,15	1,90	1,30
		CR-L-P	2,90-4,00	460	50	1,15	2,20	1,30
		CR-MAX-P	3,50-5,00	480	50	1,15	2,85	1,30



## Tractor mounting



#### Drawbar

<b>S</b> Standard • Optional	Ø22	Ø28 622	Ø28 - 0
(Replace standard)	REF. BE-2271	STANDARD	REF. BE-2887
CR	•	S	•

### Tractor connection and assembling

	Sau Carlo ID	Sal A Company ID	SAU SAU
STANDARD	REF. CMT-11	REF. CMT-6	REF. CMT-12
REF.	REF.	REF.	REF.
CMT-7	CMT-14	CMT-9	CMT-13

# Pre-installations and updates Accessories and Options

0	DESCRIPTION	OBSERVATIONS	REF.
	Pre-installation in-row weeder left side/electrohydraulic system	Including extension and cylinder	PI-011
<i>8</i>	Pre-installation solenoid valve	1 extra function double acting for ID-BASIC	PI-002
		on/off motorized tools	PI-004
	Upgrade kit for tools quick coupling		KC-002

#### Chassis **Accessories and Options**

0	DESCRIPTION	OBSERVATIONS	REF.
	Over full plate extension	*Not available for XXS and XS	SEC-12
	Solenoid valve for hydraulic extension Integrated in control box	-2	EH-EC
	Smooth Wheels assembly on the extension	Replace standard Only for M & L wheel frame models	MRE-1
11	Pivoting smooth wheels assembly on the extension	To assembly on the front or with sandy soil. Not compatible with shank F. Not compatible with shank elastomer. Replace the standard wheel frame.	MREG-1
	Pair of rear pneumatic wheels	Replaces the metal Adjustable in wheels height	RNT-P
	Hydraulic adjustment of working height	Direct to tractor, it replace the standard wheels frame	CRA-DT-1
	Incompatible with wheels mounted on extensions	Electric to replace the standard wheels frame	CRA-EC
	Three-point with tilting system	New machine replaces standard hitch frame	TSB-01
	*Replace the standard one (Inclination: +10° , -10°)	Second hand equipment	TSB-02

#### Undervine weeders Accessories and Options

	DESCRIPTION	OBSERVA	REF.	
	Standard oil cooler	Adaptable to PRO hydraulic power plant	Intake 12V	A15-01-PRO
	Pressure filter kit + oil cooler	Replaces hydraulic power plant . Not available for ID- PLUS DUAL.	Intake 12V Tractor plugs connection.	+2 KFP-03
	Hydraulic side slope correction for in- row weeders	Directly to the tractor	Unit	+2 IH-DT
	*Increases working width of 10 cm Inclination: + 21°, -10°	Electric cabine	Unit	IH-EC
	Grass bend down system	-	Right	STH-D
			Pair	STH-P
	, Ultrasensible kit for sensitive sensor	ldeal vineyards ≤ 1 cm	Unit	KU-1
02	Reinforced in row weeder cylinder for hard soil	Replaces standard cylinder. Recommended oil cooler.	Unit	CIA-R
î Î		for ID-PLUS /	Right	MD1-D
Ũ	Distance Control with cable	ID-MICRO	Pair	MD1-P
		for ID-BASIC -	Right	MD2-D
He			Pair	MD2-P
R	Electrohydraulic kit for quick- connection	In row weeder connection- disconnection	Right	KER-IA-D
	(connection-disconnection)	Not available for ID-BASIC	Pair	KER-IA-P
1	Adjustable row cleaner disc 11"	Adaptable to in-row	Right	BPI-D
<b>(</b>	(smooth disc)	weeder	Pair	BPI-P
1	Adjustable row cleaner disc 13"	Adaptable to in-row	Right	BPID-D
	(notched disc)	weeder	Pair	BPID-P
WE	Flange + Arm F + front smooth disc Ø 13 "+ double coil tines	Adaptable to frame	Right	BB001D
	*Not available for XXS y XS *It is not compatible with MREG-1		Pair	BB001P
W.	Flange + Arm F + front smooth disc Ø 16 "+ double coil tines	Adaptable to frame	Right	BB003D
	*Not available for XXS y XS *It is not compatible with MREG-1		Pair	BB003P
	Fix shank pre-undervine weeder blade	Adaptable to frame	Right	BELOO1-D
7	made of elastomer		Pair	BELO01-P

DESCRIPTION	OBSERV	ATIONS	REF.
	Ø16"	Right	ADC2D
2 mechanical disc harrow	Working with a max. width of 400mm	Pair	ADC2P
	Ø16″	Right	ADC3D
3 mechanical disc harrow	Working with a max. width of 550mm	Pair	ADC3P
Soil restraint parallelogram kit	Only to combine with weeding blade, Ø300 rotor boe	Right	LP01-D
Sold restraint parattelogram kit	ploughshare and mini-disc plow	Pair	LPO1-P
Kit ID STAR 2 discs			KIA-S2-D
Kit ID STAR 3 discs	Right	Adaptable to in-	KIA-S3-D
Kit ID STAR 2 discs	Pair	row weeder	KIA-S2-P
Kit ID STAR 3 discs			KIA-S3-P
Extra price ID-STAR (3rd disc)		Right	ID-ST23-D
Extra price ID-STAR (3rd disc)		Pair	ID-ST23-P
	2 mechanical disc harrow         3 mechanical disc harrow         Soil restraint parallelogram kit         Kit ID STAR 2 discs         Kit ID STAR 3 discs         Extra price ID-STAR (3rd disc)	2 mechanical disc harrowØ16" Working with a max. width of 400mm3 mechanical disc harrowØ16" Working with a max. width of 550mmSoil restraint parallelogram kitOnly to combine with weeding blade, Ø300 rotor hoe, ploughshare and mini-disc plowKit ID STAR 2 discsRightKit ID STAR 3 discsPairKit ID STAR 3 discsPairKit ID STAR 3 discsExtra price ID-STAR (3rd disc)	2 mechanical disc harrow       Ø16"       Right         2 mechanical disc harrow       Ø16"       Pair         3 mechanical disc harrow       Ø16"       Right         Ø16"       Working with a max. width of 400mm       Right         9 mechanical disc harrow       Ø16"       Right         Ø16"       Working with a max. width of 550mm       Pair         Ø16"       Only to combine with weeding blade, Ø300 rotor hoe, ploughshare and mini-disc plow       Right         Ø16"       Kit ID STAR 2 discs       Right       Pair         Kit ID STAR 2 discs       Right       Adaptable to inrow weeder       Adaptable to inrow weeder         Kit ID STAR 2 discs       Pair       Adaptable to inrow weeder       Adaptable to inrow weeder         Kit ID STAR 3 discs       Pair       Adaptable to inrow weeder       Pair         Kit ID STAR 3 discs       Pair       Adaptable to inrow weeder       Pair         Kit ID STAR 3 discs       Pair       Adaptable to inrow weeder       Pair         Kit ID STAR 3 discs       Pair       Adaptable to inrow weeder       Pair         Kit ID STAR 3 discs       Pair       Adaptable to inrow weeder       Pair         Kit ID STAR 3 discs       Pair       Minitian and sont so the pair       Minitian and so the pair </th

# Undervine weeders Tools for PARALLELOGRAM USE P

0	DESCRIPTION	OBSER	REF.	
3	Kit ID-ROLL Ø600	Right	Adaptable to in	KIA-R6-D
	Kit ID-ROLL Ø600	Pair	row weeder	KIA-R6-P
		CR-XS		DBR25-4-D
	Shoot remover kit + Sensor rod +	CR-S	Diaht	DBR25-5-D
	String spool	CR-M	— Right —	DBR25-6-D
	250 mm working width *Recommended oil cooler Available only for vineyards with at least 40 cm free to the ground or to any obstacle Not available on Mod. XXS and XS	CR-L		DBR25-7-D
		CR-XS	– Pair –	DBR25-4-P
		CR-S		DBR25-5-P
		CR-M		DBR25-6-P
		CR-L		DBR25-7-P
	Arm B + fixed ploughshare + Sensor rod kit	310x480x400mm	Right	BB-VFD
Action of the second se		5107480740011111	Pair	BB-VFP
	Arm C + adjustable ploughshare +	Right 410x540x430mm Pair	Right	BC-VRD
a terr	sensor rod kit		Pair	BC-VRP
AST.	Arm E + fixed ploughshare with ridging		Right	BE-VFD
A star	element + sensor rod kit		Pair	BE-VFP
	Retractable extra cleaner blade with		Right	EM-D
	spring for ploughshare		Pair	EM-P

#### Undervine weeders Tools for RADIAL USE ®

			Right	
	Arm D + weeding blade + sensor rod kit	Standard included	Pair	BD-CPD
				BD-CPP
	Kit wooding block		Cut 49 cm	RCI49D
	Kit weeding blade + sensor rod	Right	Standard 55 cm	RCI55D
			Long 65 cm	RCI65D
<u>_</u>			Cut 49 cm	RCI49P
	Kit weeding blade + sensor rod	Pair	Standard 55 cm	RCI55P
			Long 65 cm	RCI65P
×	Kit weeding blade made by Tugstene + sensor rod	Right	– Standard 55 cm –	RCHD55D
× C	Kit weeding blade made by Tugstene + sensor rod	Pair	Standard 22 cm —	RCHD55P
	Retractable extra cleaner blade "V" for		Right	EV-D
und -	blade		Pair	EV-P
 	Blade shovel		Right	VO-D
			Pair	VO-P
		CR-XS		MAD25-4-D
		CR-S	– Right –	MAD25-5-D
	Kit mini reversible plough kit 2 discs	CR-M	Right	MAD25-6-D
A-5	Ø13.5"	CR-L		MAD25-7-D
THE .	+ sensor rod	CR-XS		MAD25-4-P
	250 mm working width	CR-S		MAD25-5-P
		CR-M	Pair	MAD25-6-P
		CR-L		MAD25-7-P
	Recommended oil cooler and reinforced cylinder	CR-MAX		MAD25-8-P
		CR-S		MAD35-5-D
	Kit mini reversible plough kit 3 discs	CR-M	Right	MAD35-6-D
0515	Ø13.5"	CR-L		
	+ sensor rod	CR-S		MAD35-7-D
	250 mm working width			MAD35-5-P
<u> </u>	350 mm working width	CR-M	– Pair –	MAD35-6-P
		CR-L		MAD35-7-P
	Recommended oil cooler and reinforced cylinder	CR-MAX		MAD35-8-P
THE REAL	Retractable extra cleaner blade for		Right	EMD-D
	mini harrow disc		Pair	EMD-P
		CR-XS		RA30-4-D
		CR-S	– Right –	RA30-5-D
	Kit Rotary hoe Ø300mm +	CR-M		RA30-6-D
	sensor rod	CR-L		RA30-7-D
		CR-XS		RA30-4-P
		CR-S		RA30-5-P
	*Possibility of simultaneous use with weeding blade (not	CR-M	Pair	RA30-6-P
	included)	CR-L		RA30-7-P

0	DESCRIPTION	OBSERVA	TIONS	REF.
		CR-XS		RA40-4-D
		CR-S	Right	RA40-5-D
1	Kit Rotary hoe Ø400mm +	CR-M	ingin	RA40-6-D
	Sensor rod	CR-L		RA40-7-D
Land F. M.		CR-XS		RA40-4-P
		CR-S		RA40-5-P
		CR-M	Pair	RA40-6-P
	*Possibility of simultaneous use with weeding blade (not included)	CR-L		RA40-7-P
	Recommended oil cooler + reinforced cylinder	CR-MAX		RA40-8-P
		CR-S		RA50-5-D
	Kit Rotary hoe Ø500mm +	CR-M	Right	RA50-6-D
	Sensor rod	CR-L		RA50-7-D
C C C C C C C C C C C C C C C C C C C		CR-S		RA50-5-P
<b>T</b>		CR-M	Dair	RA50-6-P
		CR-L	Pair —	RA50-7-P
	Recommended oil cooler and reinforced cylinder	CR-MAX		RA50-8-P
		CR-XS		GS40H-4-D
		CR-S		GS40H-5-D
	Kit string mower Ø400mm +	CR-M	Right —	GS40H-6-D
	Sensor rod + String reel	CR-L		GS40H-7-D
	String reet	CR-XS	Pair	GS40H-4-P
		CR-S		GS40H-5-P
		CR-M		GS40H-6-P
		CR-L		GS40H-7-P
	*Recommended oil cooler	CR-MAX		GS40H-8-P
		CR-XS		GS50H-4-D
	Kit string mower Ø500mm + Sensor rod + String reel	CR-S		GS50H-5-D
		CR-M	Right —	GS50H-6-D
A 100 - 3		CR-L		GS50H-7-D
		CR-XS	Pair	GS50H-4-P
		CR-S		GS50H-5-P
		CR-M		GS50H-6-P
		CR-L		GS50H-7-P
	*Recommended oil cooler	CR-MAX		GS50H-8-P
	Kit string mower Ø600mm + Sensor rod +	CR-S		GS60H-5-D
		CR-M	Right	GS60H-6-D
	String reel	CR-L CR-S		<u>GS60H-7-D</u>
		CR-S CR-M	Pair It needs the	GS60H-5-P
		CR-L	system ID-PLUS	GS60H-6-P
	*Recommended oil cooler	CR-MAX	DUAL	GS60H-7-P GS60H-8-P
			Right	
	Kit for modification of string mower with boron steel blades	Only available for new machine		KSGSH-D
			Pair	KSGSH-P
	Square string spool	for mower	45 m	BHN-03
9	Nylon string blue spool	for brush head	90 m	BHN-01
	Herbicide application head	Ø500	Right	AH50D
	••		Pair	AH50P
-	Kit fix rotors Ø500 + Pair of rotors Ø400mm at undervine weeder	CR-L and CR-MAX *It needs the remote control ID-PLUS DUAL	Only available for new machine	KRFRM-P
	Packaging	Basic		EMB-1
	Packaging			

Undervine Weeding ID-NAMIC



# Ideal products and services that inspire trust, quality, experience and excellence

Specialized and customized agricultural machines with an attractive design and increasing digitalizations. Our products are oriented towards a biological, environment-friendly and precision farming.





#### INDUSTRIAS DAVID S.LU.

C/ Médico Miguel Lucas s/n CP: 30510, Yecla, Murcia-Spain Tel.: +34 968 718 119 info@id-david.com









Connect with us.

instagram.com/iddavid\_official twitter.com/IDdavidslu facebook.com/industriasdavid linkedin.com/company/id-david youtube.com/industriasdavid

www.id-david.com



