# FRONT-XL

EN

Front special frame for fruit trees equipped with 1 in-row weeder










# FRONT-XL





**Front special frame for fruit trees equipped with 1 in-row weeder.** Designed for the tillage and weeding of fruit and olive trees rows-formed.



#### PICTURE MODEL:

CF-XL + K-GSH-68 + A15C01





















- The widest range of produtcs and accessories on the market. A custom configuration to suit your needs.
- Different tools that allow both surface and tillage works up to 20 cm deep.
- The ID-CONTROL joystick allows to control all the machines manufactured by ID David and equipped with the ID-PLUS or ID-MICRO technology.

# Exclusivity

- The exclusive undervine weeder that combines the "parallelogram-radial" movement.
- Faster, safer and endowed with unmatched versatility thanks to its triple tool holder.
- Opportunity to work between plants starting from 1 cm diameter thanks to our adjustable and progressive eletronic sensor, the arm is moving at the right time to save the plant.

#### **Effectiveness**

- Time is valuable, it is possible to work up to 12 km/h with a standard soil conditions.
- The easy adjusting of hydraulic pressure of the in-row weeder assure a great work in any type of soil.
- The long hydraulic extension allows to work on large crown trees.
- Floating and tilting system for a perfect adaptation to the ground.

## (I) Reliability

- Components and materials of high quality from certified manufacturers.
- Heavy duty frame and robotic welding.
- · Great visibility of the rows.
- Experience in the manufacture of electrohydraulic undervine weeders since 1974.

# Safety

- As standard all models are fitted with an exclusive safety locking system in case of faults.
- Enables route deviations up to 30 cm in the plantation'rows.
- Our equipment incorporates easy, comfortable and safe tool replacement systems.

# **Sustainability**

- Ecological alternative to the use of herbicides.
- The low power required allows the use of small tractors with a lower carbon footprint.
- Improves the structure and porosity of the soil.

#### **Standard Equipment**

- · Includes a PRO hydraulic unit.
- · Anti-shock sensor protector.
- Extendable hoses holder.
- Hydraulic pressure regulator.
- · Electro hydraulic in row weeder.
- · Hydraulic extension 1,2 m directly to the tractor.
- · Tool kit for sensor regulation.

- Arm "D" and blade manufactured in boron steel.
- · Quick coupling kit for power tools.
- · Rotating metal depth-control wheels.
- Storage foot.
- · Floating elevation cylinder.
- Adaptable standard plate to tractor (frontal).
- +/- 10° Mechanical tilting system (hydraulic as an option).

#### Remote control type

#### **ID-PLUS**

- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

#### **ID-MICRO**

- ! NOT included the ID-CONTROL multifunction joystick. Includes ID-CONTROL multifunction joystick.
- Only for customers who already have the ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

#### **ID-BASIC**

- Includes an electric control box.
- Max. 1 additional electrohydraulic function to choose between: PI-O02 / PI-O04 / EH-EC / IH-EC / BA-EC / IFF-O1
- ! NOT allowed any updates of electro-hydraulic functions.

#### **ID-PLUS DUAL**

- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
   Includes cooler and double pump.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electrohydraulic functions.
- Includes a modular electrohydraulic system: it allows to increase the number of electrohydraulic functions.


|                |    | •x•   | ID-PLUS | ID-MICRO | ID-BASIC | ID-PLUS DUAL |
|----------------|----|-------|---------|----------|----------|--------------|
| FRONT-XL       | cm | m     | REF.    | REF.     | REF.     | REF.         |
| 1IN ROW WEEDER | 65 | ≥3,20 | CF-XL-1 | CF-XL-2  | CF-XL-3  | CF-XL-4      |





#### **Technical details**


|                    |       | А         | В    |     | 50 | L    | W    | Н    |
|--------------------|-------|-----------|------|-----|----|------|------|------|
| FRONT-XL           | REF.  | m         | m    | kg  | HP | m    | m    | m    |
| 1 IN ROW<br>WEEDER | CF-XL | 1,65-2,85 | 0,90 | 500 | 60 | 1,45 | 2,20 | 1,25 |



### **Tractor mounting**



#### **Tractor connection and assembling**



#### Chassis

### **Accessories and Options**

| <u> </u> | DESCRIPTION  | OBSERVATIONS   | REF.   |
|----------|--|--|--------|
|          | Plate for front tractor coupling                         | It will be supplied only if the corresponding form has been correctly filled out | PA-F   |
| Man.     | Solenoid valve for hydraulic extension                   | Integrated in control box  | EH-EC  |
|          | Electrohydraulic tilting frame                           |  | BA-EC  |
|          | Solenoid valve installation for electrohydraulic lifting |  | 1EE-01 |


# Pre-installations and updates Accessories and Options

| <u> </u>                        | DESCRIPTION                   | OBSERVATIONS                                | REF.   |
|---------------------------------|-------------------------------|---|--------|
| Dro                             | -installation solenoid valve  | 1 extra function double acting for ID-BASIC | PI-002 |
| Fie                             | -installation solellold valve | on/off motorized tools                      | PI-004 |
| Undervine wee<br>Accessories ar |                               |   |        |
| <u></u>                         | DESCRIPTION                   | OBSERVATIONS                                | REF.   |

| DESCRIPTION   | OBSERVAT  | REF.  |   |
|---|---|---|---|
| Standard oil cooler   | Adaptable to PRO hydraulic power plant  | Intake 12V  | A15-01-PRO  |
| Pressure filter kit + oil cooler  | Replaces hydraulic<br>power plant .<br>Not available for ID-<br>PLUS DUAL.  | Intake 12V<br>Tractor plugs<br>connection.  | KFP-03  |
| Hydraulic side slope correction for in-<br>row weeders                      | Directly to the tractor   | Unit  | H-DT  |
| *Increases working width of 10 cm<br>Inclination: + 21°, -10°               | Electric cabine   | Unit  | IH-EC   |
| Grass bend down system  |   | Right   | STH-D   |
| Ultrasensible kit for sensitive sensor                                      | Ideal vineyards ≤ 1 cm  | Unit  | KU-1  |
| Reinforced in row weeder cylinder for hard soil                             | Replaces<br>standard cylinder.<br>Recommended oil<br>cooler.  | Unit  | CIA-R   |
| Electrohydraulic kit for quick-<br>connection<br>(connection-disconnection) | In row weeder<br>connection-<br>disconnection<br>Not available for<br>ID-BASIC  | Right   | KER-IA-D  |
| Adjustable row cleaner disc 11"<br>(smooth disc)                            | Adaptable to in-row<br>weeder   | Right   | BPI-D   |
| Adjustable row cleaner disc 13" (notched disc)                              | Adaptable to in-row<br>weeder   | Right   | BPID-D  |
|   | Standard oil cooler  Pressure filter kit + oil cooler  Hydraulic side slope correction for inrow weeders  *Increases working width of 10 cm Inclination: + 21°, -10°  Grass bend down system  Ultrasensible kit for sensitive sensor  Reinforced in row weeder cylinder for hard soil  Electrohydraulic kit for quick-connection (connection-disconnection)  Adjustable row cleaner disc 11" (smooth disc)  Adjustable row cleaner disc 13" | Standard oil cooler  Pressure filter kit + oil cooler  Pressure filter kit + oil cooler  Hydraulic side slope correction for inrow weeders  *Increases working width of 10 cm Inclination: + 21°, -10°  Grass bend down system  Ultrasensible kit for sensitive sensor  Reinforced in row weeder cylinder for hard soil  Electrohydraulic kit for quick-connection (connection-disconnection)  Adjustable row cleaner disc 11″  Adaptable to in-row weeder connection-disconnection  Adjustable row cleaner disc 13″  Adaptable to in-row weeder connection-row weeder  Adaptable to in-row | Standard oil cooler  Adaptable to PRO hydraulic power plant  Replaces hydraulic power plant Intake 12V  Pressure filter kit + oil cooler  Pressure filter kit + oil cooler  Replaces hydraulic power plant Intake 12V  Tractor plugs connection.  Hydraulic side slope correction for inrow weeders  Increases working width of 10 cm lnclination: + 21°, -10°  Grass bend down system  Electric cabine  Unit  Ultrasensible kit for sensitive sensor  Ideal vineyards ≤ 1 cm  Unit  Reinforced in row weeder cylinder for hard soil  Replaces standard cylinder. Recommended oil cooler.  Recommended oil cooler.  In row weeder  connection-disconnection  In row weeder  connection-disconnection  Not available for ID-BASIC  Adjustable row cleaner disc 11"  Adaptable to in-row weeder  Right  Right |

| <u></u>  | DESCRIPTION  | OBSERVA  | ATIONS  | REF.                         |
|--|--|--|---|------------------------------|
|  | 2 mechanical disc harrow   | Ø16"<br>Working with a max.<br>width of 400mm                                      | Right   | ADC2D                        |
| With the second  | 3 mechanical disc harrow   | Ø16"<br>Working with a max.<br>width of 550mm                                      | Right   | ADC3D                        |
|  | Soil restraint parallelogram kit   | Only to combine with weeding blade, Ø300 rotor hoe, ploughshare and mini-disc plow | Right   | LP01-D                       |
| 46/7   | Kit ID STAR 2 discs  | Adaptable to in-row  |   | KIA-S2-D                     |
|  | Kit ID STAR 3 discs  | weeder   | Right —   | KIA-S3-D                     |
| The state of the s | Extra price ID-STAR (3rd disc)   |  | Right   | ID-ST23-D                    |
| Undervine<br>Tools for   | ARALLELOGRAM USE P   |  |   |                              |
|  | DESCRIPTION  | OBSERVA  | ATIONS  | REF.                         |
|  | Kit ID-ROLL Ø600   | Adaptable to in-row weeder   | Right   | KIA-R6-D                     |
| Undervine<br>Tools for   | weeders<br>ADIAL USE R   |  |   |                              |
| <u> </u>   | DESCRIPTION  | OBSERVA  | ATIONS  | REF.                         |
|  | Arm D + weeding blade + sensor rod kit   | Standard included  | Right   | BD-CPD                       |
|  | Kit right weeding blade + sensor rod   |  | Standard 55 cm  | RCI55D                       |
|  | Kit right weeding blade - sensor rod   |  | Long 65 cm  | RCI65D                       |
|  | Kit right weeding blade + sensor rod   | Recommended<br>Reinforced Cylinder   | Extra long 83 cm  | RCI83D                       |
|  |  |  | 85 cm   |                              |
|  | Kit weeding blade type Boomerang +   |  | (65E + 20I cm)  | RB6520D                      |
|  | Kit weeding blade type Boomerang + sensor rod  |  |   | RB6520D<br>RB6555D           |
|  |  |  | (65E + 20I cm)<br>120 cm  |                              |
|  | sensor rod  Kit weeding blade made by  |  | (65E + 20I cm)<br>120 cm<br>(65E + 55I cm)                          | RB6555D                      |
|  | Kit weeding blade made by Tugstene + sensor rod  Retractable extra cleaner blade "V" for   |  | (65E + 20I cm)  120 cm (65E + 55I cm)  Standard 55 cm               | RB6555D<br>RCHD55D           |
|  | Kit weeding blade made by Tugstene + sensor rod  Retractable extra cleaner blade "V" for blade  Blade shovel  Kit mini reversible plough kit 2 discs Ø13.5" + sensor rod                       | Recommended oil<br>cooler and reinforced<br>cylinder                               | (65E + 20I cm)  120 cm (65E + 55I cm)  Standard 55 cm  Right        | RB6555D<br>RCHD55D<br>EV-D   |
|  | Kit weeding blade made by Tugstene + sensor rod  Retractable extra cleaner blade "V" for blade  Blade shovel  Kit mini reversible plough kit 2 discs Ø13.5" + sensor rod  250 mm working width | cooler and reinforced  | (65E + 20I cm)  120 cm (65E + 55I cm)  Standard 55 cm  Right  Right | RB6555D  RCHD55D  EV-D  VO-D |
|  | Kit weeding blade made by Tugstene + sensor rod  Retractable extra cleaner blade "V" for blade  Blade shovel  Kit mini reversible plough kit 2 discs Ø13.5" + sensor rod                       | cooler and reinforced  | (65E + 20I cm)  120 cm (65E + 55I cm)  Standard 55 cm  Right  Right | RB6555D  RCHD55D  EV-D  VO-D |

DESCRIPTION **OBSERVATIONS** 



ID-PLUS DUAL and reinforced cylinder

Right

MAD45-3-D

REF.



Retractable extra cleaner blade for mini harrow disc

Right

EMD-D



Kit Rotary hoe Ø300mm + Sensor rod

\*Possibility of simultaneous use with weeding blade (not included)

Recommended oil cooler and reinforced cylinder

Right

RA30-3-D



Kit Rotary hoe Ø400mm + Sensor rod

\*Possibility of simultaneous use with weeding blade (not included)

Recommended oil cooler and reinforced cylinder

Right

RA40-3-D



Kit Rotary hoe Ø500mm + Sensor rod

Recommended oil cooler and reinforced cylinder

Right RA50-3-D



Kit string mower Ø500mm + Sensor rod + String reel

Recommended oil cooler

Right GS50H-3-D



Kit string mower Ø600mm + Sensor rod + String reel

Recommended oil cooler

Right GS60H-3-D



Kit string mower Ø800mm + Sensor rod + String reel

Recommended oil cooler

Right GS80H-3-D

Double string mowers and reel kit + String spool

ID PLUS DUAL control required

K-GSH-66 Ø600 + Ø800 K-GSH-68



Kit for modification of string mower with boron steel blades

Only available for new machine

Right

Ø600 + Ø600

KSGSH-D



Square string spool

for mower

Basic

45 m

BHN-03



Packaging

Airfreight- oceanfreight


EMB-3

EMB-1



# Ideal products and services that inspire trust, quality, experience and excellence

Specialized and customized agricultural machines with an attractive design and increasing digitalizations. Our products are oriented towards a biological, environment-friendly and precision farming.





#### **INDUSTRIAS DAVID S.L.U.**

C/ Médico Miguel Lucas s/n CP: 30510, Yecla, Murcia-Spain Tel.: +34 968 718 119 info@id-david.com

#### Connect with us.

instagram.com/iddavid\_official twitter.com/IDdavidslu facebook.com/industriasdavid linkedin.com/company/id-david youtube.com/industriasdavid

www.id-david.com





















