
DAVICULTOR EN

Cultivators with hydraulic width adjustment and in-row weeder
















Cultivators with hydraulic width adjustment and in-row weeder, specially designed for primary tillage in vinevards and orchards.



- Multiple tools for the in-row weeder that allow both surface working and tillage up to 20 cm deep.
- The ID-CONTROL joystick allows to control all the machines manufactured by ID David and equipped with the ID-PLUS or ID-MICRO technology.

🕀 Reliability

- · Components and materials of high quality from certified manufacturers.
- The maintenance is reduced to a minimal due to the total absence of joints and ball joints as well as the heavy duty width extensions.
- Experience in the manufacture of electrohydraulic undervine weeders since 1974

- Opportunity to work between plants starting from 1 cm diameter thanks to our adjustable and progressive eletronic sensor, the arm is moving at the right time to save the plant.
- The special position of the tines makes possible to work always at the same distance between them, whether the cultivator is completely extended or narrowed, avoiding jamming.

Safetv

- · As standard all models are fitted with an exclusive safety locking system in case of faults.
- Enables route deviations up to 30 cm in the plantation'rows.
- Our equipment incorporates easy, comfortable and safe tool replacement systems.

- The easy adjusting of hydraulic pressure of the in row weeder assured a perfect work in any type of soil.
- The reinforced structure, hydraulically width adjustable, and the special tines enable to work with different types of plougshare reaching a working depth of up to 25 cm.

Sustainability

- Ecological alternative to the use of herbicides.
- The low power required allows the use of small tractors with a lower carbon footprint.
- · Improves the structure and porosity of the soil.

Standard Equipment

- Includes a PRO hydraulic unit.
- Anti-shock sensor protector.
- Kit of Shank + Spring + Plowshare DAVID by Bellota.
- Hydraulic pressure regulator.
- Electro hydraulic in row weeder.
- Tool kit for sensor regulation.
- Arm "D" and Plough blade to weed manufactured in boron steel.

Remote control type

ID-PLUS

- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
 Includes an electronic microcontroller: allows software updates at any time.
- Up to 5 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

ID-MICRO

- ! NOT included the ID-CONTROL multifunction joystick.
 - Only for customers who already have the ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 5 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electro-hydraulic functions.

- Quick connect kit for power tools.
 - Security system under damages.
- Standard boron steel plowshare, hardness 50Hrc.
- Adjustable rear roller in height and width.
- Hydraulic width adj. direct to tractor (not available in fixed models).
- Quick attachment.

ID-BASIC

- Includes an electric control box.
- Max. 1 additional electrohydraulic function to choose between: PI-002 / PI-004 / EH-EC / TH-EC / IH-EC
- ! NOT allowed any updates of electro-hydraulic functions.

ID-PLUS DUAL


- Includes ID-CONTROL multifunction joystick.
- Includes ON-OFF of powered tools. Includes cooler and double pump.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electrohydraulic functions.
- Includes a modular electrohydraulic system: it allows to increase the number of electrohydraulic functions.


				ID-PLUS	ID-MICRO	ID-BASIC	ID-PLUS DUAL
	sel.	3	¶x¶	. 12			
DAVICULTOR	cm.	ud	m	REF.	REF.	REF.	REF.
FIX MANUAL EXTENSION 1 IN ROW WEEDER	49	2	≥ 1,10	CXF2-1-D	CXF2-2-D	CXF2-3-D	CXF2-4-D
	49	3	≥ 1,40	CXF3-1-D	CXF3-2-D	CXF3-3-D	CXF3-4-D
	55	5	≥1,90	CXF5-1-D	CXF5-2-D	CXF5-3-D	CXF5-4-D
FIX MANUAL EXTENSION 2 IN ROW WEEDER	49	2	1,10-1,50	CXF2-1-P	CXF2-2-P	CXF2-3-P	CXF2-4-P
	49	3	1,40-1,90	CXF3-1-P	CXF3-2-P	CXF3-3-P	CXF3-4-P
	55	5	1,90-2,35	CXF5-1-P	CXF5-2-P	CXF5-3-P	CXF5-4-P
HYDRAULIC EXTENSION	55	7	≥ 2,05	CXH7-1-D	CXH7-2-D	CXH7-3-D	CXH7-4-D
1 IN ROW WEEDER	55	7	≥ 2,30	CXH7A-1-D	CXH7A-2-D	CXH7A-3-D	CXH7A-4-D
р	55	9	≥ 2,25	CXH9-1-D	CXH9-2-D	CXH9-3-D	CXH9-4-D
	55	9	≥ 2,50	CXH9A-1-D	CXH9A-2-D	CXH9A-3-D	CXH9A-4-D
	55	11	≥ 2,80	CXH11-1-D	CXH11-2-D	CXH11-3-D	CXH11-4-D
X2	65	11	≥ 3,25	CXH11A-1-D	CXH11A-2-D	CXH11A-3-D	CXH11A-4-D
	65	13	≥ 3,50	CXH13-1-D	CXH13-2-D	CXH13-3-D	CXH13-4-D
HYDRAULIC EXTENSION	55	5	1,95-2,35	*CXH5-1-P	*CXH5-2-P	*CXH5-3-P	*CXH5-4-P
2 IN ROW WEEDER	55	7	2,05-2,55	CXH7-1-P	CXH7-2-P	CXH7-3-P	CXH7-4-P
	55	7	2,30-2,80	CXH7A-1-P	CXH7A-2-P	CXH7A-3-P	CXH7A-4-P
<u> </u>	55	9	2,25-2,95	CXH9-1-P	СХН9-2-Р	СХН9-3-Р	CXH9-4-P
	55	9	2,50-3,20	CXH9A-1-P	CXH9A-2-P	CXH9A-3-P	CXH9A-4-P
	55	11	2,80-3,50	CXH11-1-P	CXH11-2-P	СХН11-3-Р	CXH11-4-P
X2	65	11	3,25-3,95	CXH11A-1-P	CXH11A-2-P	CXH11A-3-P	CXH11A-4-P
	65	13	3,50-4,20	CXH13-1-P	CXH13-2-P	CXH13-3-P	CXH13-4-P


*This model hydraulically extends only the two undervines.

Technical details

		х		50	L	w	н
DAVICULTOR	REF.	m	kg	HP	m	m	m
	CXF2-D	≥ 1,10	315	20	1,90	0,70	1,30
FIX MANUAL EXTENSION 1 IN ROW WEEDER	CXF3-D	≥ 1,40	345	25	1,50	0,90	1,30
THE ROW WEEDER	CXF5-D	≥ 1,90	425	50	1,60	1,40	1,30
FIX MANUAL EXTENSION 2 IN ROW WEEDER	CXF2-P	1,10–1,50	385	25	1,90	0,70	1,30
	CXF3-P	1,40–1,90	405	30	1,50	0,90	1,30
	CXF5-P	1,90-2,35	485	55	1,60	1,40	1,30
	CXH7-D	≥ 2,05	625	55	1,65	1,70	1,30
	CXH7A-D	≥ 2,30	635	60	1,65	1,85	1,30
	СХН9-D	≥ 2,25	710	70	1,65	1,90	1,30
HYDRAULIC EXTENSION	CXH9A-D	≥ 2,50	720	75	1,65	2,05	1,30
1 IN ROW WEEDER	CXH11-D	≥ 2,80	800	85	1,65	2,45	1,30
	CXH11A-D	≥ 3,25	810	90	1,65	2,60	1,30
	CXH13-D	≥ 3,50	890	95	1,65	2,95	1,30
	СХН5-Р	1,95–2,35	505	55	1,60	1,40	1,30
	СХН7-Р	2,05-2,55	690	60	1,65	1,70	1,30
	CXH7A-P	2,30-2,80	700	65	1,65	1,85	1,30
HYDRAULIC	СХН9-Р	2,25-2,95	775	75	1,65	1,90	1,30
EXTENSION 2 IN ROW WEEDER	СХН9А-Р	2,50-3,20	785	80	1,65	2,05	1,30
	CXH11-P	2,80-3,50	860	90	1,65	2,45	1,30
	CXH11A-P	3,25-3,95	910	95	1,65	2,60	1,30
	CXH13-P	3,50-4,20	955	100	1,65	2,95	1,30







Drawbar

S Standard • Optional (Replace standard) FIX MANUAL CXF3-D		Ø22 497	Ø22	• 622 — • •	Ø28
		REF. BE-2259	BE-2271	REF. BE-2871	REF. BE-2887
	CXF3-D	S			
EXTENSION 1 IN ROW WEEDER	CXF5-D		•	S	
FIX MANUAL	CXF3-P	S			
EXTENSION 2 IN ROW WEEDER	CXF5-P		•	S	
	CXH7-D		•	S	
	CXH7A-D		•	S	
	СХН9-D		•	S	•
HYDRAULIC EXTENSION	CXH9A-D		•	S	•
1 IN ROW WEEDER	CXH11-D		•	S	•
	CXH11A-D		•	S	•
	CXH13-D		•	•	S
	CXH5-P		•	S	
	СХН7-Р		•	S	
	CXH7A-P		•	S	
HYDRAULIC	СХН9-Р		•	S	•
EXTENSION 2 IN ROW WEEDER	СХН9А-Р		•	S	•
	CXH11-P		•	S	•
	CXH11A-P		•	S	•
	CXH13-P		•	•	S



Cultivator Accessories and Options

	DESCRIPTION	OBSERVA	REF.	
	Wide plow blade with rib 330x8mm + screws	Standard included	Unitary	GA-1
	Plow blade with rib 275x8mm + screws		Unitary	GN-1
	Double coil tines 70x8mm + screws		Unitary	CM-1
0	Suppletory wings 280x8mm + screws	Adaptable to fits in double coil tines	Unitary	AL-1
	Boot+chisel+flat grid 400mm	Adaptable accessory arm		BFR400
	Additional extension (female-female)		120 mm	SE1-HH
ALL FOR THE	Cultivator reinforced spring	Replace standard spring	Unit	MRC
Collectore of	cattrator remorced spring	Extra	Unit	MRC-1
	Hydraulic 3 point hitch	Directly to the tractor	+2	TH-DT
a les		Electric control in cab (1 electrovalve)		TH-EC
10 10 10 10 10 10 10 10 10 10 10 10 10 1	Solenoid valve for hydraulic extension Integrated in control box		-2	EH-EC
1	Pair of smooth metallic wheels frontal mounting	Adjustable in height		RMD-P
		0,60 m	CXF2	ROSE
		0,97 – 1,35 m	CXF3-CXF5	R1SE
No.	f Adjustable roller Ø27cm	1,17 – 1,57 m	СХН7-СХН7А	R2SE
		1,56 - 2,36 m	СХН9-СХН9А	R4SE
		1,76 – 2,76 m	CXH11 / 11A	R5SE
	*Included as standard Height and width	2,31 – 3,31 m	CXH13 / 13A	R6SE
		0,82 m	CXF3	RFOSY
		1,05 m	CXF5	RF1SY
	Roller Ø40cm fix helical	1,40 m	CXH7-CXH7A	RF2SY
0		1,75 m	СХН9-СХН9А	RF4SY
- 198		2,25 m	CXH11 / 11A	RF5SY
	*Replaced the adjustable Ø27 roller Adjustable in height	2,50 m	CXH13 / 13A	RF6SY
		1,75 m		TT175
XX	Rear plank + Arms + Chains	2,25 m		TT225
		2,50 m		TT250
		2,75 m		TT275

0	DESCRIPTION	OBSE	OBSERVATIONS	
		0,88 m	CXF3	RPF3
- All		0,88 – 1,46 m	CXF5	RPF5
	Floating barb rake	1,48 – 2,06 m	CXH7-CXH7A	RPF7
		1,64 – 2,36 m	CXH9-CXH9A	RPF9
		2,24 - 2,96 m	CXH11 / 11A	RPF11
		2,70 - 3,41 m	CXH13 / 13A	RPF13
		0,88 m	CXF3	RP3
		0,88 – 1,46 m	CXF5	RP5
	Adapted bash value behind the values	1,48 – 2,06 m	CXH7-CXH7A	RP7
	Adapted barb rake behind the roller	1,64 – 2,36 m	CXH9-CXH9A	RP9
		2,24 – 2,96 m	CXH11 / 11A	RP11
		2,70 - 3,41 m	CXH13 / 13A	RP13

Pre-installations and updates Accessories and Options

0		DESCRIPTION	OBSERVATIONS	REF.
		Upgrade kit for tools quick coupling		KC-002
	80	Pre-installation in-row weeder left side/ electrohydraulic system		PI-001
		Pre-installation solenoid valve	1 extra function double acting for ID-BASIC	PI-002
		on/off motorized tools	PI-004	

Undervine weeders Accessories and Options

\bigcirc	DESCRIPTION	OBSERVATIONS		REF.	
	Standard oil cooler	Adaptable to PRO hydraulic power plant	Intake 12V	A15-01-PRO	
J	Pressure filter kit + oil cooler	Replaces hydraulic power plant . Not available for ID- PLUS DUAL.	Intake 12V Tractor plugs connection.	+2 KFP-03	
	Hydraulic side slope correction for in-row weeders	Directly to the tractor	Unit	+2 IH-DT	
	*Increases working width of 10 cm Inclination: + 21°, -10°	Electric cabine	Unit	IH-EC	
	Grass bend down system	_	Right	STH-D	
- CPA	Glass bend down system		Pair	STH-P	
."	Ultrasensible kit for sensitive sensor	ldeal vineyards ≤ 1 cm	Unit	KU-1	
2	Reinforced in row weeder cylinder for hard soil	Replaces standard cylinder. Recommended oil cooler.	Unit	CIA-R	

0	DESCRIPTION	OBSERVATIONS		REF.
		for ID-PLUS /	Right	MD1-D
Ϋ́λ	Distance Control with cable	ID-MICRO	Pair	MD1-P
-		for ID-BASIC	Right	MD2-D
(Fe			Pair	MD2-P
	Electrohydraulic kit for quick-connection (connection-disconnection)	In row weeder connection-	Right	KER-IA-D
		disconnection Not available for ID-BASIC	Pair	KER-IA-P

Undervine weeders Tools for PARALLELOGRAM USE P

	0	DESCRIPTION	OBSERV	ATIONS	REF.
			CXH-3 CXH-5		DBR25-11-D
			CXH-7	Right –	DBR25-5-D
		Shoot remover kit + Sensor rod +	CXH-9	Right	DBR25-6-D
_		String spool	CXH-11 CXH-13	_	DBR25-7-D
Ρ		250 mm working width	CXH-3 CXH-5		DBR25-11-P
	((((())))))))))))))))))))))))))))))))))		CXH-7		DBR25-5-P
			CXH-9	Pair	DBR25-6-P
-		*Recommended oil cooler Available only for vineyards with at least 40 cm free to the ground or to any obstacle	CXH-11 CXH-13		DBR25-7-P
Р	Cost3	Arm B + fixed ploughshare + Sensor rod kit	310x480x400mm	Right	BB-VFD
				Pair	BB-VFP
Р		Arm C + adjustable ploughshare +	410x540x430mm	Right	BC-VRD
	a the	sensor rod kit		Pair	BC-VRP
Р	the state	Arm E + fixed ploughshare with ridging		Right	BE-VFD
Ρ.		element + sensor rod kit		Pair	BE-VFP
_		Retractable extra cleaner blade with		Right	EM-D
Р		spring for ploughshare		Pair	EM-P

Undervine weeders Tools for RADIAL USE ®

_	0	DESCRIPTION	OBSER	ATIONS	REF.
R	1	Arm D + weeding blade +	Standard included	Right	BD-CPD
•	and the second	sensor rod kit	Standard Included	Pair	BD-CPP
				Cut 49 cm	RCI49D
R		Kit right weeding blade + sensor rod		Standard 55 cm	RCI55D
_	<u> </u>			Long 65 cm	RCI65D
	_			Cut 49 cm	RCI49P
R		Kit pair of weeding blade + sensor rod		Standard 55 cm	RCI55P
-				Long 65 cm	RCI65P
R		Kit weeding blade made by Tugstene + sensor rod	Right	— Standard 55 cm —	RCHD55D
R	A Contraction	Kit weeding blade made by Tugstene + sensor rod	Pair		RCHD55P

	Retractable extra cleaner blade "V" for		Right	EV-D
A.	blade		Pair	EV-P
			Right	VO-D
C. C.	Blade shovel			
			Pair	VO-P
		CXH-3 CXH-5		MAD25-11-D
	Kit mini reversible plough kit 2 discs	CXH-7	- Right -	MAD25-5-D
	Ø13.5"	CXH-9		MAD25-6-D
	+ sensor rod	CXH-11 CXH-13		MAD25-7-D
	250 mm working width	CXH-3 CXH-5		MAD25-11-P
		CXH-7	- Pair ·	MAD25-5-P
		CXH-9	Pall	MAD25-6-P
	*Recommended oil cooler and reinforced cylinder	CXH-11 CXH-13		MAD25-7-P
		CXH-3 CXH-5		MAD35-11-D
		CXH-7		MAD35-5-D
	Kit mini reversible plough kit 3 discs	CXH-9	- Right ·	MAD35-6-D
A	Ø13.5" + sensor rod	CXH-11 CXH-13		
HE	/	CXH-3 CXH-5		MAD35-7-D
	350 mm working width	СХН-7		MAD35-11-P
			- Pair ·	MAD35-5-P
		CXH-9		MAD35-6-P
	*Recommended oil cooler and reinforced cylinder	CXH-11 CXH-13		MAD35-7-P
R A	Retractable extra cleaner blade for mini		Right	EMD-D
	harrow disc		Pair	EMD-P
	Kit Rotary hoe Ø300mm + sensor rod	CXH-3 CXH-5	- Right	RA30-11-D
		CXH-7		RA30-5-D
and the		CXH-9		RA30-6-D
		CXH-11 CXH-13	Pair	RA30-7-D
		CXH-3 CXH-5 CXH-7		RA30-11-P
		CXH-9		RA30-5-P RA30-6-P
	*Possibility of simultaneous use with weeding blade (not			RASU-U-P
	included) Recommended oil cooler + reinforced cylinder	CXH-11 CXH-13		RA30-7-P
		CXH-3 CXH-5	_	RA40-11-D
		CXH-7	- Right -	RA40-5-D
	Kit Rotary hoe Ø400mm +	CXH-9		RA40-6-D
and the	Sensor rod	CXH-11 CXH-13		RA40-7-D
		CXH-3 CXH-5 CXH-7		RA40-11-P
		CXH-9	 Pair	RA40-5-P
	*Possibility of simultaneous use with weeding blade (not			RA40-6-P
	included) Recommended oil cooler + reinforced cylinder	CXH-11 CXH-13		RA40-7-P
		CXH-3 CXH-5		RA50-11-D
		CXH-7	- Right -	RA50-5-D
	Kit Rotary hoe Ø500mm +	CXH-9		RA50-6-D
S PART	Sensor rod	CXH-11 CXH-13		RA50-7-D
		CXH-3 CXH-5		RA50-11-P
		CXH-7 CXH-9	- Pair ·	RA50-5-P
		CXH-11 CXH-13		RA50-6-P

Undervine Weeding DAVICULTOR

0	DESCRIPTION	OBSERVATIO	ONS	REF.
		CXH-3 CXH-5		GS40H-11-D
	Kit string mower Ø400mm +	CXH-7	Dight	GS40H-5-D
		CXH-9	Right	GS40H-6-D
LANGE -	Sensor rod +	CXH-11 CXH-13	-	GS40H-7-D
	String reel	CXH-3 CXH-5		GS40H-11-P
<u> </u>		CXH-7		GS40H-5-P
		CXH-9	Pair	GS40H-6-P
	*Recommended oil cooler	CXH-11 CXH-13	-	GS40H-7-P
		CXH-3 CXH-5		GS50H-11-D
		CXH-7		GS50H-5-D
	Kit string mower Ø500mm +	CXH-9	Right	GS50H-6-D
	Sensor rod +	CXH-11 CXH-13	-	GS50H-7-D
	String reel	CXH-3 CXH-5		GS50H-11-P
		CXH-7	-	GS50H-5-P
		CXH-9	Pair -	GS50H-6-P
,	Recommended oil cooler	CXH-11 CXH-13		GS50H-7-P
		CXH-3 CXH-5	- Right -	GS60H-11-D
	Kit string mower Ø600mm + Sensor rod + String reel	CXH-7		GS60H-5-D
		CXH-9		GS60H-6-D
		CXH-11 CXH-13		GS60H-7-D
		CXH-3 CXH-5	- Pair -	GS60H-11-P
		CXH-7		GS60H-5-P
		CXH-9		GS60H-6-P
	D PLUS DUAL control required	CXH-11 CXH-13	-	GS60H-7-P
	Kit for modification of string mower	Only available for new	Right	KSGSH-D
	with boron steel blades	machine	Pair	KSGSH-P
	Square string spool	for mower	45 m	BHN-03
	Nylon string blue spool	for brush head	90 m	BHN-01
		Basic		EMB-1
	Packaging			



Ideal products and services that inspire trust, quality, experience and excellence

Specialized and customized agricultural machines with an attractive design and increasing digitalizations. Our products are oriented towards a biological, environment-friendly and precision farming.





INDUSTRIAS DAVID S.LU.

C/ Médico Miguel Lucas s/n CP: 30510, Yecla, Murcia-Spain Tel.: +34 968 718 119 info@id-david.com









Connect with us.

instagram.com/iddavid_official twitter.com/IDdavidslu facebook.com/industriasdavid linkedin.com/company/id-david youtube.com/industriasdavid

www.id-david.com



