ALH Front berm sweeper for pruning remains in vines and fruit trees












EN





Front berm sweeper for pruning remains in vines and fruit trees, designed to move and alline the branches resulting from pruning in a compact line to facilitate collection or mulching simultaneously with a single pass of the tractor.







🕅 Versatility

- The ID-CONTROL joystick allows to control all the machines manufactured by ID David and equipped with the ID-PLUS or ID-MICRO technology.
- It is possible to expand anytime the equiment functionality by exchanging the heads.

🕘 Reliability

- Components and materials of high quality.
- Low maintenance.
- Manufacturing experience since 1990.

🚱 Exclusivity

- Multifunction frame: berm sweeper + herbicide applicator + rotary brush + sweeper.
- The hydraulic suspension of the sweeper heads allows a perfect adaptation to the ground and extends the useful life of the brushes.

💿 Safety

- The strong frame as well as light and compact allows a perfect vision and occupies a minimum space by facilitating the turning in tight spaces.
- Sweeper heads fitted with bearings to get total protection of the motors against shocks.



PICTURE MODEL:

💮 Effectiveness

- Diameter and size of the brushes can be modified quickly and easily.
- Clean soil improves plant health, reduces the risk of illness and the use of phytosanitary products.

🕅 Sustainability

- The low power required allows the use of small tractors with a lower carbon footprint.
- Sustainable consumption: Equipment designed to be up-to-date and have a long service life.
- Aligning and mowering pruned branches improves soil quality by providing nutrients and reduce the emission of CO2 that occurs during combustion.

Standard Equipment

- Sliding tray "no grease" with adjustable nylon wheels.
- Flow regulator of the sweping turns.
- Tool for adjustment.
- Hydraulic lifting with single effect (floating system).

Remote control type

ID-PLUS

- Includes ID-CONTROL multifunction joystick.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electro-hydraulic functions.
- Includes a modular electro-hydraulic system: it allows to increase the number of electrohydraulic functions.

ID-MICRO

- ! NOT included the ID-CONTROL multifunction joystick.
- Only for customers who already have the ID-CONTROL multifunction joystick.
- Includes an electronic microcontroller: allows software updates at any time.
- Up to 4 additional electrohydraulic functions.
- Includes a modular electrohydraulic system: it allows to increase the number of electrohydraulic functions.

ID-BASIC

• Adaptable standard plate to tractor (frontal).

• Hydraulic extensions.

• Storage foot.

• Nylon blades or rubber brushes.

- Includes an electric control box.
- Hydraulic connection to the tractor by 2 hoses.
- ! NOT allowed any updates of electro-hydraulic functions.
- ! NOT allowed extra hydraulic functions.
- ! NOT included the electronic microcontroller.

DIRECT TO TRACTOR


- Includes a pipe with 1/2 male plugs for the hydraulic lift.
- Includes a pair of hoses with 1/2 male plugs for hydraulic extension.
- Includes a pair of hoses with 1/2 male connectors for ON/OFF.
- ! NOT included the ID-CONTROL multifunction joystick.
- ! NOT included the electronic microcontroller.
- ! NOT allowed extra hydraulic functions.

		• •	ID-PLUS		ID-BASIC	DIRECT TO TRACTOR
		X	1	X2	X2	Juli X6
ALH	HEAD	(m)	REF.	REF.	REF.	REF.
HALF ROW SWEEPER	K	≥4	ALH-D-P-1	ALH-D-P-2	ALH-D-P-3	ALH-D-P-5
MOTOR, LIFTING, EXTENSION		≥4	ALH-D-N-1	ALH-D-N-2	ALH-D-N-3	ALH-D-N-5
		1,70-2,30	ALH-XS-P-1	ALH-XS-P-2	ALH-XS-P-3	ALH-XS-P-5
DOUBLE ROWS SWEEPER		2,40-3,05	ALH-S-P-1	ALH-S-P-2	ALH-S-P-3	ALH-S-P-5
		2,80-3,45	ALH-SA-P-1	ALH-SA-P-2	ALH-SA-P-3	ALH-SA-P-5
ात		2,95-4,05	ALH-M-P-1	ALH-M-P-2	ALH-M-P-3	ALH-M-P-5
		3,40-4,50	ALH-L-P-1	ALH-L-P-2	ALH-L-P-3	ALH-L-P-5
		1,70-2,30	ALH-XS-N-1	ALH-XS-N-2	ALH-XS-N-3	ALH-XS-N-5
		2,20-2,60	ALH-S-N-1	ALH-S-N-2	ALH-S-N-3	ALH-S-N-5
		2,50-2,90	ALH-SA-N-1	ALH-SA-N-2	ALH-SA-N-3	ALH-SA-N-5
MOTOR,		2,60-3,50	ALH-M-N-1	ALH-M-N-2	ALH-M-N-3	ALH-M-N-5
LIFTING, EXTENSION		3,05-3,95	ALH-L-N-1	ALH-L-N-2	ALH-L-N-3	ALH-L-N-5


After Pruning

Techni	Fechnical details		А	в	c 🔅		50	L	w	н
	ALH	REF.	m	m	mm	kg	HP	m	m	m
	SINGLE	ALH-D-P	1,90-2,35	1,30	Ø300	220	40	2,30	1,00	1,30
		ALH-D-N	1,90–2,05 (*)	1,10	Ø300	220	40	2,20	1,00	1,30
	DOUBLE	ALH-XS-P	1,70-2,10	0,85	Ø100	230	40	1,70	1,00	1,30
		ALH-S-P	2,40-2,85	1,00	Ø200	240	40	1,70	1,00	1,50
		ALH-SA-P	2,80-3,25	1,00	Ø200	245	40	1,90	1,00	1,50
		ALH-M-P	2,95-3,85	1,20	Ø200	250	40	2,20	1,00	1,80
		ALH-L-P	3,40-4,30	1,30	Ø300	260	40	2,20	1,00	2,00
		ALH-XS-N	1,70–2,10 (*)	0,85	Ø100	230	40	1,70	1,00	1,30
		ALH-S-N	2,20-2,40 (*)	1,00	Ø200	240	40	1,70	1,00	1,50
		ALH-SA-N	2,50–2,75 (*)	1,00	Ø200	245	40	1,90	1,00	1,50
		ALH-M-N	2,60–3,30 (*)	1,00	Ø200	250	40	2,20	1,00	1,50
		ALH-L-N	3,05-3,75 (*)	1,10	Ø300	260	40	2,20	1,00	2,00


(*) ±20 cms with manual adjustment.



Tractor mounting



Tractor connection and assembling





Kit PRO - option

0	OBSERVATIONS		REF.		
	Allows the tool arms to be lifted	ID-PLUS and ID-MICRO	EIB-1		
	individually or simultaneously.	Direct to tractor	EIB-2		

Sweeper Accessories and Options

0	DESCRIPTION	OBSER	ATIONS	REF.
	Hydraulic power unit 60 L to 3 Point linkage	Pump 35 liters	C12	
	Standard oil cooler	Adaptable to 60 lt hydra power plant	A15-60	
	Storage Wheel Kit			KRA
			for XS	CHR1-D
	Herbicide application head with 2 nozzles	Right	for S / M / L	CHR2-D
		Pair	for XS	CHR1-P
	Width of application 55 cm	Fall	for S / M / L	CHR2-P
	Herbicide application head with 3 nozzles	Right	Not available for XS	CHR3-D
	Width of application 75 cm	Pair		CHR3-P
		Additional head	for XS	C-DBR-1-D
	250 mm right rotary brush + slide + string spool		for S / M / L	C-DBR-3-D
		Replace berm sweeper	for XS Includes arm	C-DBR-2-D
	*Advisable the C12 power unit and to note that it works only in vineyards with at least 40 cm stump free.	head	for S / M / L	C-DBR-4-D
		Additional head	for XS Includes arm	C-DBR-1-P
	250 mm pair of rotary brush + slide + string spool		for S / M / L	C-DBR-3-P
		Replace berm sweeper	for XS Includes arm	C-DBR-2-P
	*Advisable the C12 power unit and to note that it works only in vineyards with at least 40 cm stump free.	head	for S / M / L	C-DBR-4-P

ALH


After Pruning

0	DESCRIPTION	OBSERVAT	REF.		
	Nylon string blue spool	for brush head 90 m		BHN-01	
nacht that	Nylon string black spool for mower head 58 m		BHN-02		
1	Comparison dan dan adalah	1 berm sweeper head	A-EN-D		
	Supports and nylon whips	2 berm sweeper head	A-EN-P		
du.	Nylon brushes	1 berm sweeper head	EN-D		
PU B B	Nyton brushes	2 berm sweeper head		EN-P	
	Rubber blades supports	1 berm sweeper head	APG-D		
E Fer	Rubbel blades supports	2 berm sweeper head	APG-P		
Aller	Rubber brush 400 mm	1 berm sweeper head	P-40V-D		
11.	special for vineyard	2 berm sweeper head	P-40V-P		
	Reversible Rubber brush 400 x 150 mm	1 berm sweeper head	P-4015-D		
		2 berm sweeper head	P-4015-P		
	Reversible Rubber brush 500 x 200 mm	1 berm sweeper head	P-5020-D		
		2 berm sweeper head	P-5020-P		
	Plate for front tractor coupling	It will be supplied only if the corresponding form has been correctly filled out		PA-F	
	3 Points linkage	Front 3P or reversible tractor		T3P-16	
	Kit longer extension	Increases working	for 1 arm	KP2O-D	
		width of 20 cm	for 2 arms	КР20-Р	
	Control for simultaneous use of mower	for ID-PLUS / ID-MICRO		MST-01	
	with hydraulic pick-up + berm sweeper	for ID-BASIC	MST-03		
	Packaging	Basic		EMB-1	
		Airfreight- oceanfreight	EMB-3		



The value of ideas

Experience, technology, know-how and design are the fundamentals to achieving our goal: the support and full satisfaction of the farmer. Being excellent in everything we do is our guiding light.





INDUSTRIAS DAVID S.L.U.

C/ Médico Miguel Lucas s/n CP: 30510, Yecla, Murcia-Spain Tel.: +34 968 718 119 info@id-david.com









Connect with us.

instagram.com/iddavid_official twitter.com/IDdavidslu facebook.com/industriasdavid linkedin.com/company/id-david youtube.com/industriasdavid

www.id-david.com



